



## 1. PRODUCT NAME

# DELUXE 2.0 COLLECTION

## TECHNICAL DATA SHEET

## 2. MANUFACTURER

Stonepeak Ceramics, Inc.

325 W. Huron St. Ste 404, Chicago, IL 60654 US

### Production Factory:

238 Porcelain Tile Dr., Crossville, TN 38555 US

Telephone: 312.506.2800

Email: [info@stonepeakceramics.com](mailto:info@stonepeakceramics.com)

Website: [stonepeakceramics.com](http://stonepeakceramics.com)

## 3. PRODUCT DESCRIPTION

**Deluxe 2.0 Collection** – Porcelain surfaces that boast timeless elegance, drawing inspiration from natural minerals and organic elements such as sand, stone, clays and crystals. The Deluxe 2.0 collection is produced with color-body technology, showing the predominant pigment/graphic on the surface with a solid color inside. Available in honed and polished finishes, sizes 12"x24" and 24"x24" and offers decorative mosaics and trim pieces. Ideal for floor and wall applications and suitable for both residential and commercial settings.

### Recommended Applications:

Ideally suited for commercial and residential floors and walls.

### Finishes/Textures:

- Color Body
- Rectified

### Sizes/Thickness:

24" x 24" x 5/16" nominal \*(8 mm)

12" x 24" x 5/16" nominal \*(8 mm)

*\*Denotes work size per ISO 10545-2.*

### Recommended Grout Joint: 3/32" or greater.

Grout joints of 1/8" inch or less, especially with larger format tiles or running bond patterns, may require floor flatness values in excess of the 1/4" in 10' (or 1/16" in 1.0') standard required by ANSI.

For patterns with running bond/brick joints, Stonepeak recommends a maximum of 33% offset.

## Stonepeak Ceramics Trim System

A 4"x24" bullnose, 6"x12" cove base and 2"x2" mosaics on the 12"x12" mesh sheet are available to complete a variety of design aesthetics.

Refer to **Stonepeak Ceramics Product Catalog**.

## 4. TECHNICAL DATA

Physical Properties	ASTM Test	Industry Standards	Stonepeak Results
Water Absorption	C373	Impervious < 0.5 %	≤ 0.5%
Thickness	C499	Range ± 0.04 Inc. Max	≤ ± 0.04 Inch
Dimension	C499	± 0.25%	≤ ± 0.25%
Facial Dimension	C499	Range - 0.30% /+ 0.40%	≤ ± 0.40%
Warpage Average Diagonal	C485	Range - 0.30% /+ 0.40%	≤ ± 0.40%
Warpage Average Edge	C485	± 0.25%	≤ ± 0.25%
Wedging	C502	≥ 50 psi	≥ 50 psi
Bond Strength	C482	≥ 250 lbf	≥ 250 lbf
Breaking Strength	C648	Range 0 - 10	≥ 7
Hardness (Mohs)	C1895	No Requirement; Range 0 - 5	Class 5
Visible Abrasion Resistance for Glazed tiles	C1027	No sample must show alterations to surface	No evidence of Damage
Frost Resistance	C1026	No Requirement; Range E - A	Class A / Unaffected
Chemical Resistance	C650	No Requirement; Range E - A	Class A
Stain Resistance	C1378	≥ 0.42	≥ 0.42
DCOF (Matte/Honed)	ANSI A 326.3	No Requirement; Range V0 - V4	V2
Aesthetic Class/Shade Rating	Visual Evaluation Shade & Texture		

(1) All values given are for Matte/Honed finish. Values for different finishes are available upon request.

(2) DCOF results referring to matte and/or textured products are performed with the WET test, while for polished and silky the DCOF test is performed dry.

(3) Glazed tiles.

## 5. INSTALLATION

### Surface preparations:

All installation work using Stonepeak Ceramics' tiles will conform to the standards set forth in the latest version of ANSI A108/118 and/or the TCNA Handbook for Ceramic Tile installations.

All substrates should be between 40 degrees F and 90 degrees F and structurally sound, clean and free of all dirt, oil, grease, paint, concrete sealers or curing compounds as per ANSI A108.01.

**Deflection:**

Substrate must conform to all state and local building code requirements and ANSI A108.01 for maximum allowable substrate deflection

**Movement joints:**

Movement joints shall be provided throughout the tile and work will conform to ANSI Specification A108.01-3.7; A108.02 – 4.4. and TCNA Details EJ171.

**Installation or setting materials:**

Setting materials used will conform to the ANSI 118.4 standard or greater and be recommended by the selected manufacturer for the installation & setting materials for ceramic or porcelain tile based on the application requirements.

## 6. AVAILABILITY AND COST

**Deluxe 2.0 Collection** is available from selected distributors of ceramic tile.

To find accessible information of delivery and product costs for your area, please contact your nearest Stonepeak Ceramics distributor.

See our website the find a distributor near you:

[http://www.stonepeakceramics.com/services-where\\_to\\_buy.php](http://www.stonepeakceramics.com/services-where_to_buy.php)

## 7. WARRANTY

**Stonepeak Ceramics** guarantees that its products will be free of manufacturing defects and they will meet or exceed the performance specifications set forth in ANSI 137.1.

For further information and details please contact your nearest Stonepeak Ceramics Distributor for a written copy of the warranty information.

For distributor information go to our website:

[http://www.stonepeakceramics.com/services-where\\_to\\_buy.php](http://www.stonepeakceramics.com/services-where_to_buy.php)

## 8. MAINTENANCE

**Care and Maintenance Recommendations Guide.**

Please refer to **Stonepeak Ceramics Care and Maintenance Recommendations Guide** for all technical information as to the care of this collection.

## 9. TECHNICAL SERVICES

**Technical Assistance**

Guide Specifications, literature, SDS, tile samples, details and installation procedures are all available for your use or libraries.


Please contact your nearest Stonepeak representative for catalogues or physical samples.

**Continued Education Programs** are available – 1- or 2-hour **HSW Learning Units** – contact Stonepeak Ceramics' main office to set up a presentation.


## 10. FILING SYSTEMS

**Deluxe 2.0 Collection**


Perla




Crema



Delorian Grey



Ocean Storm



Absolute Black

## 11. ENVIRONMENTAL CERTIFICATIONS

Stonepeak proudly contain factory and product certifications:



## 12. RECYCLED CONTENT

Products certified by Bureau Veritas. Please ask to see certifications.